



NOTE : ADDITIONAL REQUIREMENTS FOR SAFETY GLASS ARE REQUIRED WHERE BALUSTRADE IS MORE THAN 5 metres ABOVE FLOOR / GROUND. REFER AS. 1288 / AMDT 2 / 2011-11-11, CLAUSE 3.8

AZD2 (SCALE 1:2)

DESIGN HORIZONTAL LIVE LOAD = 0.75 kN/m
 APPLICABLE FOR WIND REGIONS A & B TO AS.1170, TERRAIN CATEGORY 2
 REGION A MAXIMUM BUILDING HEIGHT 50 m
 REGION B MAXIMUM BUILDING HEIGHT 10 m

B	REFERENCE FOR GLAZING ABOVE 5m AMENDED	24.11.2014
A	ISSUED FOR CONSTRUCTION	09.01.2014
REV	COMMENTS	DATE

AXIOM GROUP P.O. BOX 94, WERRIBEE VIC. 3030 PH. 1300 652 336 FAX. 1300 611 789 EMAIL. sales@axiomgroup.com.au WEB. axiomgroup.com.au	
DESIGNED	IKF
DRAWN	AB
REF No	ROLL No.

CLIVE STEEL PARTNERS PTY LTD
 CONSULTING ENGINEERS - STRUCTURAL & CIVIL



BUILDING 6
 62/195 WELLINGTON ROAD
 CLAYTON, VICTORIA
 AUSTRALIA. 3168
 Telephone (03) 9545 0223
 Facsimile (03) 9545 3022
 Email csp@clivesteel.com.au
 A.C.N. 005 363 735 A.B.N. 92 627 427 761

METROPOLIS (BASE MOUNT) 'AZD2' CANTILEVERED GLASS BALUSTRADE	
TIMBER MOUNT	
DRG. No.	16996 - T - S12
REV.	B